



Daphne Magplus AM 30

High Performance Neat Cutting Oil

Description

A non-active, **Chlorine Free** and **Low Mist** neat cutting oil formulated with highly refined mineral base oil and various additives such as: non-active type sulphur extreme pressure additive and fatty oil which give excellent cutting performance even for high temperature cutting operations.

Application

Excellent as a cutting oil for carbon steels and alloy steels. Also suitable for cutting non-ferrous metal such as copper and brass. It is recommended for most cutting processes such as: auto-lathe work, turning, milling, threading and gear cutting.

Characteristics

1. Provides High Quality Surface Finish And Accuracy.
2. Extends Tooling Life Due To Its High Lubricity.
3. Eliminates Chlorine Corrosion On Machines And Finished Parts.
4. Good Flushing And Cooling Properties.
5. Low Oil Mist Helps To Improve Working Environment.

Packing

20L pail, 200L drum

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement. Please refer to Material Safety Data Sheet for any safety issue concern which can be obtained from your nearest Idemitsu reseller.



Typical Specifications

Daphne Magplus AM 30

	ASTM METHOD	
Colour	D-1500	L2.0
Density 15 °C g/cm ³	D-4052	0.8724
Viscosity, cSt @ 40 °C	D-445	30.10
100°C		5.612
Flash Point (COC), °C	D-92	234
Viscosity Index	D-2270	127
Total Acid No. (mgKOH/g)	D-664	0.06
Copper Corrosion (100 °Cx3hrs)	D-130	1b

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement. Please refer to Material Safety Data Sheet for any safety issue concern which can be obtained from your nearest Idemitsu reseller.